



# PREFABRICATED REINFORCING WELDED ELEMENT ARMACERO




NMX-B-456, NMX-B-253,  
NMX-B-072



Is a reinforcement consisting of longitudinal and transverse wires welded together through resistance. Often it used as steel reinforcement in beams and columns.

It is supplied in sheets to wholesalers, who assemble the columns and distribute them through sub-wholesalers and retailers.

## ▶ Specifications

	Desing	Type		
		Type 1 / G-60	2R	3E
	10X10-3	X		
	12X12-3	X		
	15X15-3	X		
	12x12-4	X		
	15x15-4	X	X	X
	12x20-4	X		
	15x20-4	X	X	X
	15x25-4	X	X	
	15x30-4	X	X	

Type	Diameter	
	longitudinal G-60	transversal G-50
Type 1 G-60	5.72 mm	3.60 mm
2R	7.25 mm	4.88 mm
3E	8.37 mm	4.88 mm

**NOTE:** Additionally, the Reinforced Column (LAB plant) is offered.

These products earn the following LEED® credits thanks to regional, recycled material content



**LEED® v4**  
**Prerequisite MRp:**  
Construction and demolition waste management planning.

- **Credit M12:** Construction Waste Management.
- **Building Product disclosure:**
  - Material ingredients
  - Sourcing of raw materials

- **MCR2:** Construction Waste Management.
- **MRC4:** Recycled Content.
- **MRC5:** Reegional Materials.